

Product Configuration Options

OrderCode:	IED-EP+/DAUT/E1-DRL/E33014110010-C00-AE												
Platform: IED-EP+ EuroProt+ platform			Type: DAUT Special automation & control					Configuration: E1-DRL Numerical arc suppression coil controller automation					
Platform specific options	Position	0	1	2	3	4	5	6	7	8	9	10	11
	Value	E	3	3	0	1	4	1	1	0	0	1	0
Config specific options	Position	0	1	2									
	Value	E	0	0									
Checksum	AE												
Detailed platform specific options													
Platform version												Position 0	
Current version												E	
Power Supply												Position 1	
24V												0	
48V												1	
60V												2	
110V												3	
220/230V												4	
I/O modules												Position 2	
24V												0	
48V												1	
60V												2	
110V (125V)												3	
220V												4	
110VAC												5	
230VAC												6	
Mounting methods												Position 3	
Rack												0	
Flush mounting												1	
Wall mounting												2	
Semi-flush												3	
IP54 rated mounting												4	
Wall mounting with terminals												5	

No mounting	6
Fold-down mounting	7
Fold-down mounting with terminals	8
CPU first communication port	Position 4
N/A	0
Fiber optical Ethernet MM/ST	1
Fiber optical Ethernet MM/LC	2
Fiber optical Ethernet SM/FC	3
RJ-45 Ethernet	4
2xMM/LC with PRP/HSR	5
2xSFP with PRP/HSR	6
2xRJ-45 with PRP/HSR	7
2xSFP without PRP/HSR	8
CPU secondary communication port	Position 5
N/A	0
Fiber optical Ethernet MM/ST	1
Fiber optical Ethernet MM/LC	2
Fiber optical Ethernet SM/FC	3
RJ-45 Ethernet	4
Serial POF	5
Serial glass fiber	7
RS-485/422	8
Front panel communication port	Position 6
RJ-45	1
LCD size	Position 7
N/A	0
3.5	1
5.7	2
IEC61850 protocol (additional charge)	Position 8
No	0
Yes	1
Customization service (additional charge)	Position 9
No	0
Yes	1
CyberProtect functionality	Position 10

No	1
Yes	2
Secondary language	Position 11
None	0
HUN	1
GER	2
RUS	3
ITA(N/A)	4
FRA	5
ROU	6
ESP	7
Detailed config specific options	
Configuration version	Position 0
Current version	C
I/O module in position N	Position 1
N/A	0
O8	1
O12	2
O16	3
R4	4
R8	5
R12	6
R16	7
ATO	8
Type of potentiometer	Position 2
200 Ohm	0
1000 Ohm	1