

Product Configuration Options

OrderCode:		IED-EP+/DGYD/E34-CBBP_F/D3301311000-B22000000200-E0														
Platform: IED-EP+ EuroProt+ platform				Type: DGYD Centralized busbar protection						Configuration: E34-CBBP_F Centralized three-phase busbar protection for 4 bays in 84HP rack size. (Numbers of binary I/O in the standard configuration: 8BOut, 24Bin.)						
Platform specific options		Position	0	1	2	3	4	5	6	7	8	9	10			
		Value	D	3	3	0	1	3	1	1	0	0	0			
Config specific options		Position	0	1	2	3	4	5	6	7	8	9	10	11		
		Value	D	2	2	0	0	0	0	0	0	2	0	0		
Checksum		E0														
Detailed platform specific options																
Platform version														Position 0		
Current version														D		
Power Supply														Position 1		
24V														0		
48V														1		
60V														2		
110V														3		
220/230V														4		
I/O modules														Position 2		
24V														0		
48V														1		
60V														2		
110V (125V)														3		
220V														4		
110VAC														5		
230VAC														6		
Mounting methods														Position 3		
Rack														0		
Flush mounting														1		
Wall mounting														2		
Semi-flush														3		
IP54 rated mounting														4		

Wall mounting with terminals	5
No mounting	6
Fold-down mounting	7
Fold-down mounting with terminals	8
CPU first communication port	Position 4
N/A	0
Fiber optical Ethernet MM/ST	1
Fiber optical Ethernet SM/FC	2
PRP/HSR MM/LC	3
Fiber optical Ethernet MM/LC	4
RJ-45	5
CPU secondary communication port	Position 5
N/A	0
Fiber optical Ethernet MM/ST	1
Fiber optical Ethernet SM/FC	2
RJ-45 Ethernet	3
Serial POF	4
Serial Double ring POF	5
Serial glass fiber	6
RS-485/422	7
Fiber optical Ethernet MM/LC	8
Front panel communication port	Position 6
RJ-45	1
LCD size	Position 7
N/A	0
3.5	1
5.7	2
IEC61850 protocol (additional charge)	Position 8
No	0
Yes	1
Customization service (additional charge)	Position 9
No	0
Yes	1
Secondary language	Position 10
None	0

HUN	1
GER	2
RUS	3
ITA(N/A)	4
FRA	5
ROU	6
ESP	7
Detailed config specific options	
Configuration version	Position 0
Current version	B
Default binary input module	Position 1
N/A	0
O8	1
O12	2
O16	3
O6R5	4
Default binary output module	Position 2
N/A	0
R4	1
R8	2
R12	3
R16	4
Input module in position E	Position 3
N/A	0
O8	1
O12	2
O16	3
O9S+BNC	4
O9S+MM/ST	5
Input module in position D	Position 4
N/A	0
O8	1
O12	2
O16	3
RTD	4

Binary input module in position C	Position 5
N/A	0
O8	1
O12	2
O16	3
I/O module in position G	Position 6
N/A	0
O8	1
O12	2
O16	3
R4	4
R8	5
R12	6
R16	7
I/O module in position I	Position 7
N/A	0
O8	1
O12	2
O16	3
R4	4
R8	5
R12	6
R16	7
Number of NC contacts (R8,R12,R16)	Position 8
0	0
1	1
2	2
4	3
8	4
Trip contacts	Position 9
0	0
4	1
8	2
12	3
16	4

20	5
24	6
Number of bus sections	Position 10
1	0
2	1
3	2
4	3
Voltage breakdown condition	Position 11
N/A	0
Yes	1