

### Product Configuration Options

<b>OrderCode:</b>	IED-EP+/DTIVA/E2-Feeder_H/E33014110010-C202700020000-F2													
<b>Platform:</b> IED-EP+ EuroProt+ platform	<b>Type:</b> DTIVA Feeder protections					<b>Configuration:</b> E2-Feeder_H Non-directional three-phase, directional residual overcurrent protection, control & automation device (Numbers of binary I/O in the standard configuration: 8BOut, 12Bin.)<								
<b>Platform specific options</b>	Position	0	1	2	3	4	5	6	7	8	9	10	11	
	Value	E	3	3	0	1	4	1	1	0	0	1	0	
<b>Config specific options</b>	Position	0	1	2	3	4	5	6	7	8	9	10	11	12
	Value	E	2	0	2	7	0	0	0	2	0	0	0	0
<b>Checksum</b>	F2													
<b>Detailed platform specific options</b>														
<b>Platform version</b>													<b>Position 0</b>	
Current version													E	
<b>Power Supply</b>													<b>Position 1</b>	
24V													0	
48V													1	
60V													2	
110V													3	
220/230V													4	
<b>I/O modules</b>													<b>Position 2</b>	
24V													0	
48V													1	
60V													2	
110V (125V)													3	
220V													4	
110VAC													5	
230VAC													6	
<b>Mounting methods</b>													<b>Position 3</b>	
Rack													0	
Flush mounting													1	
Wall mounting													2	
Semi-flush													3	
IP54 rated mounting													4	

Wall mounting with terminals	5
No mounting	6
Fold-down mounting	7
Fold-down mounting with terminals	8
<b>CPU first communication port</b>	<b>Position 4</b>
N/A	0
Fiber optical Ethernet MM/ST	1
Fiber optical Ethernet MM/LC	2
Fiber optical Ethernet SM/FC	3
RJ-45 Ethernet	4
2xMM/LC with PRP/HSR	5
2xSFP with PRP/HSR	6
<b>CPU secondary communication port</b>	<b>Position 5</b>
N/A	0
Fiber optical Ethernet MM/ST	1
Fiber optical Ethernet MM/LC	2
Fiber optical Ethernet SM/FC	3
RJ-45 Ethernet	4
Serial POE	5
Serial glass fiber	7
RS-485/422	8
<b>Front panel communication port</b>	<b>Position 6</b>
RJ-45	1
RJ-45 remote HMI with 3m cabel	2
<b>LCD size</b>	<b>Position 7</b>
N/A	0
3.5	1
5.7	2
<b>IEC61850 protocol (additional charge)</b>	<b>Position 8</b>
No	0
Yes	1
<b>Customization service (additional charge)</b>	<b>Position 9</b>
No	0
Yes	1
<b>CyberProtect functionality</b>	<b>Position 10</b>

No	1
Yes	2
<b>Secondary language</b>	<b>Position 11</b>
None	0
HUN	1
GER	2
RUS	3
ITA(N/A)	4
FRA	5
ROU	6
<b>Detailed config specific options</b>	
<b>Configuration version</b>	<b>Position 0</b>
Current version	C
<b>Type of Power Supply module</b>	<b>Position 1</b>
PS	1
PSTP (inc.2xTRIP)	2
<b>I/O module in position B (42HP)</b>	<b>Position 2</b>
N/A	0
O8	1
O12	2
O15	4
O6R5	5
R4	6
R8+00	7
R8+80	8
R8+C0	9
R12+0000	10
R12+4000	11
R12+4400	12
RTD	13
AIC	14
ATO	15
4xTRIP	17
O9S+BNC	19
O9S+MM/ST	20

<b>I/O module in position C (42HP - O12)</b>	<b>Position 3</b>
N/A	0
O8	1
O12	2
O15	4
O6R5	5
R4	6
R8+00	7
R8+80	8
R8+C0	9
R12+0000	10
R12+4000	11
R12+4400	12
RTD	13
AIC	14
ATO	15
4xTRIP	17
O9S+BNC	19
O9S+MM/ST	20
<b>I/O module in position D (42HP - R8)</b>	<b>Position 4</b>
N/A	0
O8	1
O12	2
O15	4
O6R5	5
R4	6
R8+00	7
R8+80	8
R8+C0	9
R12+0000	10
R12+4000	11
R12+4400	12
RTD	13
AIC	14
ATO	15

4xTRIP	17
O9S+BNC	19
O9S+MM/ST	20
<b>I/O module in position E (42HP - TRIP)</b>	<b>Position 5</b>
N/A	0
O8	1
O12	2
O15	4
O6R5	5
R4	6
R8+00	7
R8+80	8
R8+C0	9
R12+0000	10
R12+4000	11
R12+4400	12
RTD	13
AIC	14
ATO	15
4xTRIP	17
O9S+BNC	19
O9S+MM/ST	20
<b>I/O module in position F (42HP)</b>	<b>Position 6</b>
N/A	0
O8	1
O12	2
O15	4
O6R5	5
R4	6
R8+00	7
R8+80	8
R8+C0	9
R12+0000	10
R12+4000	11
R12+4400	12

RTD	13
AIC	14
ATO	15
4xTRIP	17
O9S+BNC	19
O9S+MM/ST	20
<b>I/O module in position G (42HP)</b>	<b>Position 7</b>
N/A	0
O8	1
O12	2
O15	4
O6R5	5
R4	6
R8+00	7
R8+80	8
R8+C0	9
R12+0000	10
R12+4000	11
R12+4400	12
RTD	13
AIC	14
ATO	15
4xTRIP	17
O9S+BNC	19
O9S+MM/ST	20
<b>CT module</b>	<b>Position 8</b>
CT+5151	1
CT+5153	2
CT+5115	3
<b>CT terminal type</b>	<b>Position 9</b>
Conventional	0
Ring-lug	1
<b>VT terminal type</b>	<b>Position 10</b>
Conventional	0
<b>Busbar protection sub-unit</b>	<b>Position 11</b>

No	0
Yes	1
<b>SW option</b>	<b>Position 12</b>
N/A	0