

Product Configuration Options

OrderCode:	IED-EP+/DTIVA/E3-Feeder_H/D3301311000-C102600000-BA											
Platform: IED-EP+ EuroProt+ platform			Type: DTIVA Feeder protections			Configuration: E3-Feeder_H Directional 3Ph+Io overcurrent, over- undervoltage, frequency protection and autorecloser in 42HP rack size. (Numbers of binary I/O in the standard configuration: 8BOut, 12BIn.)						
Platform specific options	Position	0	1	2	3	4	5	6	7	8	9	10
	Value	D	3	3	0	1	3	1	1	0	0	0
Config specific options	Position	0	1	2	3	4	5	6	7	8	9	
	Value	D	1	0	2	6	0	0	0	0	0	
Checksum	BA											
Detailed platform specific options												
Platform version												Position 0
Current version												D
Power Supply												Position 1
24V												0
48V												1
60V												2
110V												3
220/230V												4
I/O modules												Position 2
24V												0
48V												1
60V												2
110V (125V)												3
220V												4
110VAC												5
230VAC												6
Mounting methods												Position 3
Rack												0
Flush mounting												1
Wall mounting												2
Semi-flush												3
IP54 rated mounting												4

Wall mounting with terminals	5
No mounting	6
Fold-down mounting	7
Fold-down mounting with terminals	8
CPU first communication port	Position 4
N/A	0
Fiber optical Ethernet MM/ST	1
Fiber optical Ethernet SM/FC	2
PRP/HSR MM/LC	3
Fiber optical Ethernet MM/LC	4
CPU secondary communication port	Position 5
N/A	0
Fiber optical Ethernet MM/ST	1
Fiber optical Ethernet SM/FC	2
RJ-45 Ethernet	3
Serial POF	4
Serial Double ring POF	5
Serial glass fiber	6
RS-485/422	7
Fiber optical Ethernet MM/LC	8
Front panel communication port	Position 6
RJ-45	1
RJ-45 remote HMI with 3m cabel	2
LCD size	Position 7
N/A	0
3.5	1
5.7	2
IEC61850 protocol (additional charge)	Position 8
No	0
Yes	1
Customization service (additional charge)	Position 9
No	0
Yes	1
Secondary language	Position 10
None	0

HUN	1
GER	2
RUS	3
ITA(N/A)	4
FRA	5
ROU	6
ESP	7
Detailed config specific options	
Configuration version	Position 0
Current version	C
Type of Power Supply module	Position 1
PS	0
PSTP (inc.2xTRIP)	1
I/O module in position B	Position 2
N/A	0
O8	1
O12	2
O16	3
R4	4
R8+00	5
R8+80	6
R8+C0	7
R12+0000	8
R12+4000	9
R12+4400	10
R16+0000	11
R16+8000	12
R16+8080	13
RTD	14
AIC	15
ATO	16
I/O module in position C	Position 3
N/A	0
O8	1
O12	2

O16	3
R4	4
R8+00	5
R8+80	6
R8+C0	7
R12+0000	8
R12+4000	9
R12+4400	10
R16+0000	11
R16+8000	12
R16+8080	13
RTD	14
AIC	15
ATO	16
I/O module in position D	Position 4
N/A	0
4xTRIP	1
O8	2
O12	3
O16	4
R4	5
R8+00	6
R8+80	7
R8+C0	8
R12+0000	9
R12+4000	10
R12+4400	11
R16+0000	12
R16+8000	13
R16+8080	14
I/O module in position E	Position 5
N/A	0
O8	1
O12	2
O16	3

R4	4
R8+00	5
R8+80	6
R8+C0	7
R12+0000	8
R12+4000	9
R12+4400	10
R16+0000	11
R16+8000	12
R16+8080	13
O9S+BNC	14
O9S+MM/ST	15
4xTRIP	16
I/O module in position F	Position 6
N/A	0
4xTRIP	1
O8	2
O12	3
O16	4
O6R5	5
R4	6
R8+00	7
R8+80	8
R8+C0	9
R12+0000	10
R12+4000	11
R12+4400	12
R16+0000	13
R16+8000	14
R16+8080	15
I/O module in position G	Position 7
N/A	0
4xTRIP	1
O8	2
O12	3

O16	4
O6R5	5
R4	6
R8+00	7
R8+80	8
R8+C0	9
R12+0000	10
R12+4000	11
R12+4400	12
R16+0000	13
R16+8000	14
R16+8080	15
CT module in position I	Position 8
CT+5151	0
CT+5153	1
Busbar protection sub-unit	Position 9
No	0
Yes	2