

### Product Configuration Options

<b>OrderCode:</b>	IED-EP+/DTIVA/E5-Feeder_F/E33014110010-D200002070000000200020-3E																						
<b>Platform:</b> IED-EP+ EuroProt+ platform	<b>Type:</b> DTIVA Feeder protections											<b>Configuration:</b> E5-Feeder_F MV line differential protection in 84HP rack size. (Numbers of binary I/O in the standard configuration: 8BOut, 12BIn.)											
<b>Platform specific options</b>	Position	0	1	2	3	4	5	6	7	8	9	10	11										
	Value	E	3	3	0	1	4	1	1	0	0	1	0										
<b>Config specific options</b>	Position	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21
	Value	E	2	0	0	0	0	2	0	7	0	0	0	0	0	0	2	0	0	0	2	0	
<b>Checksum</b>	3E																						
<b>Detailed platform specific options</b>																							
<b>Platform version</b>																							<b>Position 0</b>
Current version																							E
<b>Power Supply</b>																							<b>Position 1</b>
24V																							0
48V																							1
60V																							2
110V																							3
220/230V																							4
<b>I/O modules</b>																							<b>Position 2</b>
24V																							0
48V																							1
60V																							2
110V (125V)																							3
220V																							4
110VAC																							5
230VAC																							6
<b>Mounting methods</b>																							<b>Position 3</b>
Rack																							0
Flush mounting																							1
Wall mounting																							2
Semi-flush																							3
IP54 rated mounting																							4

Wall mounting with terminals	5
No mounting	6
Fold-down mounting	7
Fold-down mounting with terminals	8
<b>CPU first communication port</b>	<b>Position 4</b>
N/A	0
Fiber optical Ethernet MM/ST	1
Fiber optical Ethernet MM/LC	2
Fiber optical Ethernet SM/FC	3
RJ-45 Ethernet	4
2xMM/LC with PRP/HSR	5
2xSFP with PRP/HSR	6
<b>CPU secondary communication port</b>	<b>Position 5</b>
N/A	0
Fiber optical Ethernet MM/ST	1
Fiber optical Ethernet MM/LC	2
Fiber optical Ethernet SM/FC	3
RJ-45 Ethernet	4
Serial POF	5
Serial glass fiber	7
RS-485/422	8
<b>Front panel communication port</b>	<b>Position 6</b>
RJ-45	1
RJ-45 remote HMI with 3m cabel	2
<b>LCD size</b>	<b>Position 7</b>
N/A	0
3.5	1
5.7	2
<b>IEC61850 protocol (additional charge)</b>	<b>Position 8</b>
No	0
Yes	1
<b>Customization service (additional charge)</b>	<b>Position 9</b>
No	0
Yes	1
<b>CyberProtect functionality</b>	<b>Position 10</b>

No	1
Yes	2
<b>Secondary language</b>	<b>Position 11</b>
None	0
HUN	1
GER	2
RUS	3
ITA(N/A)	4
FRA	5
ROU	6
<b>Detailed config specific options</b>	
<b>Configuration version</b>	<b>Position 0</b>
Current version	D
<b>Type of Power Supply module</b>	<b>Position 1</b>
PS	1
PSTP (inc.2xTRIP)	2
<b>I/O module in position C (84HP)</b>	<b>Position 2</b>
N/A	0
O8	1
O12	2
O15	4
O6R5	5
R4	6
R8+00	7
R8+80	8
R8+C0	9
R12+0000	10
R12+4000	11
R12+4400	12
RTD	13
AIC	14
ATO	15
4xTRIP	17
O9S+BNC	19
O9S+MM/ST	20

<b>I/O module in position D (84HP)</b>	<b>Position 3</b>
N/A	0
O8	1
O12	2
O15	4
O6R5	5
R4	6
R8+00	7
R8+80	8
R8+C0	9
R12+0000	10
R12+4000	11
R12+4400	12
RTD	13
AIC	14
ATO	15
4xTRIP	17
O9S+BNC	19
O9S+MM/ST	20
<b>I/O module in position E (84HP)</b>	<b>Position 4</b>
N/A	0
O8	1
O12	2
O15	4
O6R5	5
R4	6
R8+00	7
R8+80	8
R8+C0	9
R12+0000	10
R12+4000	11
R12+4400	12
RTD	13
AIC	14
ATO	15

4xTRIP	17
O9S+BNC	19
O9S+MM/ST	20
<b>I/O module in position F (84HP)</b>	<b>Position 5</b>
N/A	0
<b>I/O module in position G (84HP - O12)</b>	<b>Position 6</b>
N/A	0
O8	1
O12	2
O15	4
O6R5	5
R4	6
R8+00	7
R8+80	8
R8+C0	9
R12+0000	10
R12+4000	11
R12+4400	12
RTD	13
AIC	14
ATO	15
4xTRIP	17
O9S+BNC	19
O9S+MM/ST	20
<b>I/O module in position H (84HP)</b>	<b>Position 7</b>
N/A	0
O8	1
O12	2
O15	4
O6R5	5
R4	6
R8+00	7
R8+80	8
R8+C0	9
R12+0000	10

R12+4000	11
R12+4400	12
RTD	13
AIC	14
ATO	15
4xTRIP	17
O9S+BNC	19
O9S+MM/ST	20
<b>I/O module in position I (84HP - R8)</b>	<b>Position 8</b>
N/A	0
O8	1
O12	2
O15	4
O6R5	5
R4	6
R8+00	7
R8+80	8
R8+C0	9
R12+0000	10
R12+4000	11
R12+4400	12
RTD	13
AIC	14
ATO	15
4xTRIP	17
O9S+BNC	19
O9S+MM/ST	20
<b>I/O module in position J (84HP)</b>	<b>Position 9</b>
N/A	0
O8	1
O12	2
O15	4
O6R5	5
R4	6
R8+00	7

R8+80	8
R8+C0	9
R12+0000	10
R12+4000	11
R12+4400	12
RTD	13
AIC	14
ATO	15
4xTRIP	17
O9S+BNC	19
O9S+MM/ST	20
<b>I/O module in position K (84HP)</b>	<b>Position 10</b>
N/A	0
O8	1
O12	2
O15	4
O6R5	5
R4	6
R8+00	7
R8+80	8
R8+C0	9
R12+0000	10
R12+4000	11
R12+4400	12
RTD	13
AIC	14
ATO	15
4xTRIP	17
O9S+BNC	19
O9S+MM/ST	20
<b>I/O module in position L (84HP - TRIP)</b>	<b>Position 11</b>
N/A	0
O8	1
O12	2
O15	4

O6R5	5
R4	6
R8+00	7
R8+80	8
R8+C0	9
R12+0000	10
R12+4000	11
R12+4400	12
RTD	13
AIC	14
ATO	15
4xTRIP	17
O9S+BNC	19
O9S+MM/ST	20
<b>I/O module in position M (84HP)</b>	<b>Position 12</b>
N/A	0
O8	1
O12	2
O15	4
O6R5	5
R4	6
R8+00	7
R8+80	8
R8+C0	9
R12+0000	10
R12+4000	11
R12+4400	12
RTD	13
AIC	14
ATO	15
4xTRIP	17
O9S+BNC	19
O9S+MM/ST	20
<b>I/O module in position N (84HP)</b>	<b>Position 13</b>
N/A	0



O8	1
O12	2
O15	4
O6R5	5
R4	6
R8+00	7
R8+80	8
R8+C0	9
R12+0000	10
R12+4000	11
R12+4400	12
RTD	13
AIC	14
ATO	15
4xTRIP	17
O9S+BNC	19
O9S+MM/ST	20
<b>I/O module in position O (84HP)</b>	<b>Position 14</b>
N/A	0
O8	1
O12	2
O15	4
O6R5	5
R4	6
R8+00	7
R8+80	8
R8+C0	9
R12+0000	10
R12+4000	11
R12+4400	12
RTD	13
AIC	14
ATO	15
4xTRIP	17
O9S+BNC	19

O9S+MM/ST	20
<b>I/O module in position P (84HP)</b>	<b>Position 15</b>
N/A	0
O8	1
O12	2
O15	4
O6R5	5
R4	6
R8+00	7
R8+80	8
R8+C0	9
R12+0000	10
R12+4000	11
R12+4400	12
RTD	13
AIC	14
ATO	15
4xTRIP	17
O9S+BNC	19
O9S+MM/ST	20
<b>CT module</b>	<b>Position 16</b>
CT+5151	1
CT+5153	2
CT+5115	3
<b>CT terminal type</b>	<b>Position 17</b>
Conventional	0
Ring-lug	1
<b>VT terminal type</b>	<b>Position 18</b>
Conventional	0
<b>2nd CT module (DTIVA)</b>	<b>Position 19</b>
N/A	0
protection	1
measurement	2
<b>Line differential communication (84HP)</b>	<b>Position 20</b>
N/A	0

---

CPU PB - MM/ST (0-2km)	1
CPU PB - SM/FC (0-50km)	2
CPU PB - SM/FC (10-120km)	3
2xDir COM - SM/FC (0-50km)	4
2xDir COM - SM/FC (10-120km)	5
G.703 (E0)	6
2xSFP	7
<b>SW option</b>	<b>Position 21</b>
N/A	0