

Product Configuration Options

OrderCode:	IED-EP+/DTRV/E3-TR_H/D3301311000-B220002000-46											
Platform: IED-EP+ EuroProt+ platform			Type: DTRV Transformer & (generator) protection					Configuration: E3-TR_H 2 winding transformer differential protection with automatic voltage regulator in 42HP rack size. (Numbers of binary I/O in the standard configuration: 8BOut, 12BIn.)				
Platform specific options	Position	0	1	2	3	4	5	6	7	8	9	10
	Value	D	3	3	0	1	3	1	1	0	0	0
Config specific options	Position	0	1	2	3	4	5	6	7	8	9	
	Value	D	2	2	0	0	0	2	0	0	0	
Checksum	46											
Detailed platform specific options												
Platform version												Position 0
Current version												D
Power Supply												Position 1
24V												0
48V												1
60V												2
110V												3
220/230V												4
I/O modules												Position 2
24V												0
48V												1
60V												2
110V (125V)												3
220V												4
110VAC												5
230VAC												6
Mounting methods												Position 3
Rack												0
Flush mounting												1
Wall mounting												2
Semi-flush												3
IP54 rated mounting												4

Wall mounting with terminals	5
No mounting	6
Fold-down mounting	7
Fold-down mounting with terminals	8
CPU first communication port	Position 4
N/A	0
Fiber optical Ethernet MM/ST	1
Fiber optical Ethernet SM/FC	2
PRP/HSR MM/LC	3
Fiber optical Ethernet MM/LC	4
RJ-45	5
CPU secondary communication port	Position 5
N/A	0
Fiber optical Ethernet MM/ST	1
Fiber optical Ethernet SM/FC	2
RJ-45 Ethernet	3
Serial POF	4
Serial Double ring POF	5
Serial glass fiber	6
RS-485/422	7
Fiber optical Ethernet MM/LC	8
Front panel communication port	Position 6
RJ-45	1
LCD size	Position 7
N/A	0
3.5	1
5.7	2
IEC61850 protocol (additional charge)	Position 8
No	0
Yes	1
Customization service (additional charge)	Position 9
No	0
Yes	1
Secondary language	Position 10
None	0

HUN	1
GER	2
RUS	3
ITA(N/A)	4
FRA	5
ROU	6
ESP	7
Detailed config specific options	
Configuration version	Position 0
Current version	B
Default binary input module	Position 1
N/A	0
O8	1
O12	2
O16	3
O6R5	4
Default binary output module	Position 2
N/A	0
R4	1
R8	2
R12	3
R16	4
I/O module in position E	Position 3
N/A	0
O8	1
O12	2
O16	3
R4	4
R8	5
R12	6
R16	7
O9S+BNC	8
O9S+MM/ST	9
ATO	10
AIC	11

I/O module in position B	Position 4
N/A	0
O8	1
O12	2
O16	3
R4	4
R8	5
R12	6
R16	7
RTD	8
AIC	9
Number of NC contacts (R8,R12,R16)	Position 5
0	0
1	1
2	2
4	3
8	4
Trip contacts	Position 6
0	0
2	1
4	2
6	3
8	4
12	5
CT module (TR Prim)	Position 7
CT+5151	0
CT+5153	3
CT module	Position 8
CT+5151	0
CT+5153	3
Inrush current minimizer function	Position 9
N/A	0
Yes	1