

Product Configuration Options

OrderCode:	IED-EP+/DVEZ/E1-BCU_H/D3301311000-A0000000000-2C											
Platform: IED-EP+ EuroProt+ platform			Type: DVEZ Bay control			Configuration: E1-BCU_H Bay control unit in 42HP rack size. (Numbers of binary I/O in the standard configuration: 0BOut, 0BIn.)						
Platform specific options	Position	0	1	2	3	4	5	6	7	8	9	10
	Value	D	3	3	0	1	3	1	1	0	0	0
Config specific options	Position	0	1	2	3	4	5	6	7	8	9	10
	Value	D	0	0	0	0	0	0	0	0	0	0
Checksum	2C											
Detailed platform specific options												
Platform version												Position 0
Current version												D
Power Supply												Position 1
24V												0
48V												1
60V												2
110V												3
220/230V												4
I/O modules												Position 2
24V												0
48V												1
60V												2
110V (125V)												3
220V												4
110VAC												5
230VAC												6
Mounting methods												Position 3
Rack												0
Flush mounting												1
Wall mounting												2
Semi-flush												3
IP54 rated mounting												4
Wall mounting with terminals												5

No mounting	6
Fold-down mounting	7
Fold-down mounting with terminals	8
CPU first communication port	Position 4
N/A	0
Fiber optical Ethernet MM/ST	1
Fiber optical Ethernet SM/FC	2
PRP/HSR MM/LC	3
Fiber optical Ethernet MM/LC	4
CPU secondary communication port	Position 5
N/A	0
Fiber optical Ethernet MM/ST	1
Fiber optical Ethernet SM/FC	2
RJ-45 Ethernet	3
Serial POF	4
Serial Double ring POF	5
Serial glass fiber	6
RS-485/422	7
Fiber optical Ethernet MM/LC	8
Front panel communication port	Position 6
RJ-45	1
RJ-45 remote HMI with 3m cabel	2
LCD size	Position 7
N/A	0
3.5	1
5.7	2
IEC61850 protocol (additional charge)	Position 8
No	0
Yes	1
Customization service (additional charge)	Position 9
No	0
Yes	1
Secondary language	Position 10
None	0
HUN	1

GER	2
RUS	3
ITA(N/A)	4
FRA	5
ROU	6
ESP	7
Detailed config specific options	
Configuration version	Position 0
Current version	A
I/O module in position B	Position 1
N/A	0
O8	1
O12	2
O16	3
R4	4
R8	5
R12	6
R16	7
I/O module in position C	Position 2
N/A	0
O8	1
O12	2
O16	3
R4	4
R8	5
R12	6
R16	7
I/O module in position D	Position 3
N/A	0
O8	1
O12	2
O16	3
R4	4
R8	5
R12	6

R16	7
I/O module in position E	Position 4
N/A	0
O8	1
O12	2
O16	3
R4	4
R8	5
R12	6
R16	7
O9S+BNC	8
O9S+MM/ST	9
ATO	10
AIC	11
I/O module in position F	Position 5
N/A	0
O8	1
O12	2
O16	3
R4	4
R8	5
R12	6
R16	7
RTD	8
O6R5	9
AIC	10
I/O module in position G	Position 6
N/A	0
O8	1
O12	2
O16	3
R4	4
R8	5
R12	6
R16	7

I/O module in position H	Position 7
N/A	0
O8	1
O12	2
O16	3
R4	4
R8	5
R12	6
R16	7
RTD	8
AIC	9
O6R5	10
I/O module in position I	Position 8
N/A	0
O8	1
O12	2
O16	3
R4	4
R8	5
R12	6
R16	7
Number of NC contacts (R8,R12,R16)	Position 9
0	0
1	1
2	2
4	3
8	4
Binary signal transmission	Position 10
N/A	0
CPU PB - SM/FC (0-50km)	1
CPU PB - MM/ST (0-2km)	2
3xDir COM - SM/FC (0-50km)	3
3xDir COM - MM/ST (0-2km)	4
G.703	5
CPU PB - SM/FC (10-120km)	6

3xDir COM - SM/FC (10-120km)	7
2xDir COM - SM/FC (0-50km)	8