

Product Configuration Options

OrderCode:	IED-EP+/DVEZ/E2-BCU_H/E33014110010-B1027000000000-1D														
Platform: IED-EP+ EuroProt+ platform	Type: DVEZ Bay control					Configuration: E2-BCU_H Bay control unit with measurement function. Special HW configuration, in 42HP rack size.									
Platform specific options	Position	0	1	2	3	4	5	6	7	8	9	10	11		
	Value	E	3	3	0	1	4	1	1	0	0	1	0		
Config specific options	Position	0	1	2	3	4	5	6	7	8	9	10	11	12	13
	Value	E	1	0	2	7	0	0	0	0	0	0	0	0	0
Checksum	1D														
Detailed platform specific options															
Platform version													Position 0		
Current version													E		
Power Supply													Position 1		
24V													0		
48V													1		
60V													2		
110V													3		
220/230V													4		
I/O modules													Position 2		
24V													0		
48V													1		
60V													2		
110V (125V)													3		
220V													4		
110VAC													5		
230VAC													6		
Mounting methods													Position 3		
Rack													0		
Flush mounting													1		
Wall mounting													2		
Semi-flush													3		
IP54 rated mounting													4		
Wall mounting with terminals													5		

No mounting	6
Fold-down mounting	7
Fold-down mounting with terminals	8
CPU first communication port	Position 4
N/A	0
Fiber optical Ethernet MM/ST	1
Fiber optical Ethernet MM/LC	2
Fiber optical Ethernet SM/FC	3
RJ-45 Ethernet	4
2xMM/LC with PRP/HSR	5
2xSFP with PRP/HSR	6
2xRJ-45 with PRP/HSR	7
CPU secondary communication port	Position 5
N/A	0
Fiber optical Ethernet MM/ST	1
Fiber optical Ethernet MM/LC	2
Fiber optical Ethernet SM/FC	3
RJ-45 Ethernet	4
Serial POE	5
Serial glass fiber	7
RS-485/422	8
Front panel communication port	Position 6
RJ-45	1
LCD size	Position 7
N/A	0
3.5	1
5.7	2
IEC61850 protocol (additional charge)	Position 8
No	0
Yes	1
Customization service (additional charge)	Position 9
No	0
Yes	1
CyberProtect functionality	Position 10
No	1

Yes	2
Secondary language	Position 11
None	0
HUN	1
GER	2
RUS	3
ITA(N/A)	4
FRA	5
ROU	6
ESP	7
Detailed config specific options	
Configuration version	Position 0
Current version	B
Type of Power Supply module (no PSTP)	Position 1
PS	1
PS+/2161	5
I/O module in position B (42HP)	Position 2
N/A	0
O8	1
O12	2
O12+2101	3
O15	4
O6R5	5
R4	6
R8+00	7
R8+80	8
R8+C0	9
R12+0000	10
R12+4000	11
R12+4400	12
RTD	13
AIC	14
ATO	15
4xTRIP	17
O9S+BNC	19

O9S+MM/ST	20
I/O module in position C (42HP - O12)	Position 3
N/A	0
O8	1
O12	2
O12+2101	3
O15	4
O6R5	5
R4	6
R8+00	7
R8+80	8
R8+C0	9
R12+0000	10
R12+4000	11
R12+4400	12
RTD	13
AIC	14
ATO	15
4xTRIP	17
O9S+BNC	19
O9S+MM/ST	20
I/O module in position D (42HP - R8)	Position 4
N/A	0
O8	1
O12	2
O12+2101	3
O15	4
O6R5	5
R4	6
R8+00	7
R8+80	8
R8+C0	9
R12+0000	10
R12+4000	11
R12+4400	12

RTD	13
AIC	14
ATO	15
4xTRIP	17
O9S+BNC	19
O9S+MM/ST	20
I/O module in position E (42HP - TRIP)	Position 5
N/A	0
O8	1
O12	2
O12+2101	3
O15	4
O6R5	5
R4	6
R8+00	7
R8+80	8
R8+C0	9
R12+0000	10
R12+4000	11
R12+4400	12
RTD	13
AIC	14
ATO	15
4xTRIP	17
4xTRIP (no TCS)	18
O9S+BNC	19
O9S+MM/ST	20
I/O module in position F (E2-BCU)	Position 6
N/A	0
O8	1
O12	2
O15	4
O6R5	5
R4	6
R8+00	7

R8+80	8
R8+C0	9
R12+0000	10
R12+4000	11
R12+4400	12
RTD	13
AIC	14
ATO	15
4xTRIP	17
O9S+BNC	19
O9S+MM/ST	20
CT+/5115	24
CT+/1500	25
VT+/2211	26
I/O module in position G (E2-BCU)	Position 7
N/A	0
O8	1
O12	2
O15	4
O6R5	5
R4	6
R8+00	7
R8+80	8
R8+C0	9
R12+0000	10
R12+4000	11
R12+4400	12
RTD	13
AIC	14
ATO	15
4xTRIP	17
O9S+BNC	19
O9S+MM/ST	20
CT+/5115	24
CT+/1500	25

VT+/2211	26
I/O module in position H (E2-BCU)	Position 8
N/A	0
O8	1
O12	2
O15	4
O6R5	5
R4	6
R8+00	7
R8+80	8
R8+C0	9
R12+0000	10
R12+4000	11
R12+4400	12
RTD	13
AIC	14
ATO	15
4xTRIP	17
O9S+BNC	19
O9S+MM/ST	20
CT+/5115	24
CT+/1500	25
VT+/2211	26
I/O module in position I (E2-BCU)	Position 9
N/A	0
O8	1
O12	2
O15	4
O6R5	5
R4	6
R8+00	7
R8+80	8
R8+C0	9
R12+0000	10
R12+4000	11

R12+4400	12
RTD	13
AIC	14
ATO	15
4xTRIP	17
O9S+BNC	19
O9S+MM/ST	20
CT+/5115	24
CT+/1500	25
VT+/2211	26
CT terminal type	Position 10
Conventional	0
Ring-lug	1
VT terminal type	Position 11
Conventional	0
Binary signal transmission (42HP)	Position 12
N/A	0
CPU PB - MM/ST (0-2km)	1
CPU PB - SM/FC (0-50km)	2
CPU PB - SM/FC (10-120km)	3
2xDir COM - SM/FC (0-50km)	4
2xDir COM - SM/FC (10-120km)	5
3xDir COM - MM/ST (0-2km)	6
3xDir COM - SM/FC (0-50km)	7
3xDir COM - SM/FC (10-120km)	8
G.703	9
SW option	Position 13
N/A	0