

Product Configuration Options

OrderCode:	IED-EP+/OGYD/E5-DBBP/E33014110010-B10270000-3F												
Platform: IED-EP+ EuroProt+ platform	Type: OGYD Decentralized busbar protection						Configuration: E5-DBBP Distributed busbar protection for 15 sub-units in 84HP rack size. (Numbers of binary I/O in the standard configuration: 8BOut, 12BIn.)						
Platform specific options	Position	0	1	2	3	4	5	6	7	8	9	10	11
	Value	E	3	3	0	1	4	1	1	0	0	1	0
Config specific options	Position	0	1	2	3	4	5	6	7	8			
	Value	E	1	0	2	7	0	0	0	0			
Checksum	3F												
Detailed platform specific options													
Platform version												Position 0	
Current version												E	
Power Supply												Position 1	
24V												0	
48V												1	
60V												2	
110V												3	
220/230V												4	
I/O modules												Position 2	
24V												0	
48V												1	
60V												2	
110V (125V)												3	
220V												4	
110VAC												5	
230VAC												6	
Mounting methods												Position 3	
Rack												0	
Flush mounting												1	
Wall mounting												2	
Semi-flush												3	
IP54 rated mounting												4	

Wall mounting with terminals	5
No mounting	6
Fold-down mounting	7
Fold-down mounting with terminals	8
CPU first communication port	Position 4
N/A	0
Fiber optical Ethernet MM/ST	1
Fiber optical Ethernet MM/LC	2
Fiber optical Ethernet SM/FC	3
RJ-45 Ethernet	4
2xMM/LC with PRP/HSR	5
2xSFP with PRP/HSR	6
2xRJ-45 with PRP/HSR	7
2xSFP without PRP/HSR	8
CPU secondary communication port	Position 5
N/A	0
Fiber optical Ethernet MM/ST	1
Fiber optical Ethernet MM/LC	2
Fiber optical Ethernet SM/FC	3
RJ-45 Ethernet	4
Serial POE	5
Serial glass fiber	7
RS-485/422	8
Front panel communication port	Position 6
RJ-45	1
LCD size	Position 7
N/A	0
3.5	1
5.7	2
IEC61850 protocol (additional charge)	Position 8
No	0
Yes	1
Customization service (additional charge)	Position 9
No	0
Yes	1

CyberProtect functionality	Position 10
No	1
Yes	2
Secondary language	Position 11
None	0
HUN	1
GER	2
RUS	3
ITA(N/A)	4
FRA	5
ROU	6
ESP	7
Detailed config specific options	
Configuration version	Position 0
Current version	B
Type of Power Supply module (no PSTP)	Position 1
PS	1
PS+/2161	5
I/O module in position C (84HP)	Position 2
N/A	0
O8	1
O12	2
O12+2101	3
O15	4
O6R5	5
R4	6
R8+00	7
R8+80	8
R8+C0	9
R12+0000	10
R12+4000	11
R12+4400	12
RTD	13
AIC	14
ATO	15

4xTRIP	17
O9S+BNC	19
O9S+MM/ST	20
I/O module in position D (84HP)	Position 3
N/A	0
O8	1
O12	2
O12+2101	3
O15	4
O6R5	5
R4	6
R8+00	7
R8+80	8
R8+C0	9
R12+0000	10
R12+4000	11
R12+4400	12
RTD	13
AIC	14
ATO	15
4xTRIP	17
O9S+BNC	19
O9S+MM/ST	20
I/O module in position E (84HP)	Position 4
N/A	0
O8	1
O12	2
O12+2101	3
O15	4
O6R5	5
R4	6
R8+00	7
R8+80	8
R8+C0	9
R12+0000	10

R12+4000	11
R12+4400	12
RTD	13
AIC	14
ATO	15
4xTRIP	17
O9S+BNC	19
O9S+MM/ST	20
I/O module in position F (84HP)	Position 5
N/A	0
I/O module in position G (84HP - O12)	Position 6
N/A	0
O8	1
O12	2
O12+2101	3
O15	4
O6R5	5
R4	6
R8+00	7
R8+80	8
R8+C0	9
R12+0000	10
R12+4000	11
R12+4400	12
RTD	13
AIC	14
ATO	15
4xTRIP	17
O9S+BNC	19
O9S+MM/ST	20
I/O module in position H	Position 7
N/A	0
O8	1
O12	2
O12+2101	3

O15	4
O6R5	5
R4	6
R8+00	7
R8+80	8
R8+C0	9
R12+0000	10
R12+4000	11
R12+4400	12
RTD	13
AIC	14
ATO	15
4xTRIP	17
4xTRIP (no TCS)	18
O9S+BNC	19
O9S+MM/ST	20
SW option	Position 8
N/A	0