

Product Configuration Options

OrderCode:	IED-EP+ S/S24/Variant 1/D3300-E2000500000010-36														
Platform: IED-EP+ S Smart line IED EP+	Type: S24 S24 Smart Line series					Configuration: Variant 1 3Ph+Io overcurrent, motor protection and autorecloser in 24HP industrial enclosure.									
Platform specific options	Position	0	1	2	3	4									
	Value	D	3	3	0	0									
Config specific options	Position	0	1	2	3	4	5	6	7	8	9	10	11	12	13
	Value	D	2	0	0	0	5	0	0	0	0	0	0	1	0
Checksum	36														
Detailed platform specific options															
Platform version															Position 0
Current version															D
Power Supply															Position 1
24V															0
48V															1
60V															2
110V															3
220/230V															4
I/O modules															Position 2
24V															0
48V															1
60V															2
110V (125V)															3
220V															4
110VAC															5
230VAC															6
Mounting methods															Position 3
Flush mounting															0
Din rail mounting															1
Secondary language															Position 4
None															0
HUN															1
GER															2

RUS	3
ITA(N/A)	4
FRA	5
ROU	6
ESP	7
Detailed config specific options	
Configuration version	Position 0
Current version	E
Type of Power Supply module (S24)	Position 1
PSTP (2xTRIP)	2
Display type	Position 2
B&W	0
3.5" vertical	1
CPU first communication port	Position 3
N/A	0
Fiber optical ethernet MM/ST	1
Fiber optical ethernet SM/FC	2
Fiber optical Ethernet MM/LC	3
RJ-45	4
CPU secondary communication port	Position 4
N/A	0
Fiber optical Ethernet MM/ST	1
Fiber optical Ethernet SM/FC	2
RJ-45	3
Serial POF	4
Serial glass fiber	5
RS-485/422	6
Fiber optical Ethernet MM/LC	7
I/O module in position D	Position 5
N/A	0
O8	1
O12	2
O15	4
O6R5	5
R4	6

R8+00	7
R8+80	8
R12+0000	10
R12+4000	11
4xTRIP	17
I/O module in position E	Position 6
N/A	0
O8	1
O12	2
O15	4
O6R5	5
R4	6
R8+00	7
R8+80	8
R12+0000	10
R12+4000	11
RTD	13
CT module in position B	Position 7
CT+5151	0
CT+5153	1
CT terminal type	Position 8
Conventional	0
Ring-lug	1
Capacitor bank protection	Position 9
N/A	0
Yes	1
IEC61850 protocol (additional charge)	Position 10
No	0
Yes	1
Customization service (additional charge)	Position 11
No	0
Yes	1
CyberProtect functionality	Position 12
No	1
Yes	2

SW option	Position 13
N/A	0