

Product Configuration Options

| | | | | | | | | | | | | | |
|--|---|---|---|---|--|---|---|---|---|---|---|----|-------------------|
| OrderCode: | IED-EP+ S/S24/Variant 2/C3300-F00000000000-4B | | | | | | | | | | | | |
| Platform: IED-EP+ S Smart line IED EP+ | Type: S24 S24 Smart Line series | | | | Configuration: Variant 2 Vectorjump, over- underpower, frequency protection and autorecloser in 24HP industrial enclosure. | | | | | | | | |
| Platform specific options | Position | 0 | 1 | 2 | 3 | 4 | | | | | | | |
| | Value | C | 3 | 3 | 0 | 0 | | | | | | | |
| Config specific options | Position | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 |
| | Value | C | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Checksum | 4B | | | | | | | | | | | | |
| Detailed platform specific options | | | | | | | | | | | | | |
| Platform version | | | | | | | | | | | | | Position 0 |
| Current version | | | | | | | | | | | | | C |
| Power Supply | | | | | | | | | | | | | Position 1 |
| 24V | | | | | | | | | | | | | 0 |
| 48V | | | | | | | | | | | | | 1 |
| 60V | | | | | | | | | | | | | 2 |
| 110V | | | | | | | | | | | | | 3 |
| 220/230V | | | | | | | | | | | | | 4 |
| I/O modules | | | | | | | | | | | | | Position 2 |
| 24V | | | | | | | | | | | | | 0 |
| 48V | | | | | | | | | | | | | 1 |
| 60V | | | | | | | | | | | | | 2 |
| 110V | | | | | | | | | | | | | 3 |
| 220V | | | | | | | | | | | | | 4 |
| 110VAC | | | | | | | | | | | | | 5 |
| 230VAC | | | | | | | | | | | | | 6 |
| Mounting methods | | | | | | | | | | | | | Position 3 |
| Flush mounting | | | | | | | | | | | | | 0 |
| Din rail mounting | | | | | | | | | | | | | 1 |
| Secondary language | | | | | | | | | | | | | Position 4 |
| None | | | | | | | | | | | | | 0 |
| HUN | | | | | | | | | | | | | 1 |
| GER | | | | | | | | | | | | | 2 |

| | |
|---|-------------------|
| RUS | 3 |
| ITA(N/A) | 4 |
| FRA | 5 |
| ROU | 6 |
| Detailed config specific options | |
| Configuration version | Position 0 |
| Current version | F |
| Display type | Position 1 |
| B&W | 0 |
| 3.5" vertical | 1 |
| CPU first communication port | Position 2 |
| N/A | 0 |
| Fiber optical ethernet MM/ST | 1 |
| Fiber optical ethernet SM/FC | 2 |
| Fiber optical Ethernet MM/LC | 3 |
| CPU secondary communication port | Position 3 |
| N/A | 0 |
| Fiber optical Ethernet MM/ST | 1 |
| Fiber optical Ethernet SM/FC | 2 |
| RJ-45 | 3 |
| Serial POF | 4 |
| Serial glass fiber | 5 |
| RS-485/422 | 6 |
| Fiber optical Ethernet MM/LC | 7 |
| I/O module in position D | Position 4 |
| O6R5 | 0 |
| O8 | 1 |
| O12 | 2 |
| R8+00 | 3 |
| R8+80 | 4 |
| R8+C0 | 5 |
| R12+0000 | 6 |
| R12+4000 | 7 |
| R12+4400 | 8 |
| I/O module in position E | Position 5 |

| | |
|--|--------------------|
| N/A | 0 |
| O8 | 1 |
| O12 | 2 |
| R8+00 | 3 |
| R8+80 | 4 |
| R8+C0 | 5 |
| R12+0000 | 6 |
| R12+4000 | 7 |
| R12+4400 | 8 |
| O6R5 | 9 |
| CT module in position B | Position 6 |
| CT+5151 | 0 |
| CT+5153 | 1 |
| Nominal voltage of VT module | Position 7 |
| 100/200V AC | 0 |
| 230V AC | 1 |
| Restricted Earth Fault | Position 8 |
| N/A | 0 |
| Yes | 1 |
| Capacitor bank protection | Position 9 |
| N/A | 0 |
| Yes | 1 |
| IEC61850 protocol (additional charge) | Position 10 |
| No | 0 |
| Yes | 1 |
| Customization service (additional charge) | Position 11 |
| No | 0 |
| Yes | 1 |