

Product Configuration Options

OrderCode:	IED-EP+ S/S24/Variant 2/D3300-G200050000000010-DB																	
Platform: IED-EP+ S Smart line IED EP+	Type: S24 S24 Smart Line series								Configuration: Variant 2 Vectorjump, over- underpower, frequency protection and autorecloser in 24HP industrial enclosure.									
Platform specific options	Position	0	1	2	3	4												
	Value	D	3	3	0	0												
Config specific options	Position	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
	Value	D	2	0	0	0	5	0	0	0	0	0	0	0	0	0	1	0
Checksum	DB																	
Detailed platform specific options																		
Platform version																	Position 0	
Current version																	D	
Power Supply																	Position 1	
24V																	0	
48V																	1	
60V																	2	
110V																	3	
220/230V																	4	
I/O modules																	Position 2	
24V																	0	
48V																	1	
60V																	2	
110V (125V)																	3	
220V																	4	
110VAC																	5	
230VAC																	6	
Mounting methods																	Position 3	
Flush mounting																	0	
Din rail mounting																	1	
Secondary language																	Position 4	
None																	0	
HUN																	1	
GER																	2	

RUS	3
ITA(N/A)	4
FRA	5
ROU	6
ESP	7
Detailed config specific options	
Configuration version	Position 0
Current version	G
Type of Power Supply module (S24)	Position 1
PSTP (2xTRIP)	2
Display type	Position 2
B&W	0
3.5" vertical	1
CPU first communication port	Position 3
N/A	0
Fiber optical ethernet MM/ST	1
Fiber optical ethernet SM/FC	2
Fiber optical Ethernet MM/LC	3
RJ-45	4
CPU secondary communication port	Position 4
N/A	0
Fiber optical Ethernet MM/ST	1
Fiber optical Ethernet SM/FC	2
RJ-45	3
Serial POF	4
Serial glass fiber	5
RS-485/422	6
Fiber optical Ethernet MM/LC	7
I/O module in position D	Position 5
N/A	0
O8	1
O12	2
O15	4
O6R5	5
R4	6

R8+00	7
R8+80	8
R12+0000	10
R12+4000	11
4xTRIP	17
I/O module in position E	Position 6
N/A	0
O8	1
O12	2
O15	4
O6R5	5
R4	6
R8+00	7
R8+80	8
R12+0000	10
R12+4000	11
RTD	13
CT module in position B	Position 7
CT+5151	0
CT+5153	1
CT terminal type	Position 8
Conventional	0
Ring-lug	1
VT terminal type	Position 9
Conventional	0
Nominal voltage of VT module	Position 10
100/200V AC	0
230V AC	1
Restricted Earth Fault	Position 11
N/A	0
Yes	1
Capacitor bank protection	Position 12
N/A	0
Yes	1
IEC61850 protocol (additional charge)	Position 13

No	0
Yes	1
Customization service (additional charge)	Position 14
No	0
Yes	1
CyberProtect functionality	Position 15
No	1
Yes	2
SW option	Position 16
N/A	0