

Product Configuration Options

OrderCode:	IED-EP+ S/S24/Variant 4/C3300-B000000000-CF										
Platform: IED-EP+ S Smart line IED EP+		Type: S24 S24 Smart Line series			Configuration: Variant 4 MV line differential protection and autorecloser in 24HP industrial enclosure.						
Platform specific options	Position	0	1	2	3	4					
	Value	C	3	3	0	0					
Config specific options	Position	0	1	2	3	4	5	6	7	8	9
	Value	C	0	0	0	0	0	0	0	0	0
Checksum	CF										
Detailed platform specific options											
Platform version											Position 0
Current version											C
Power Supply											Position 1
24V											0
48V											1
60V											2
110V											3
220/230V											4
I/O modules											Position 2
24V											0
48V											1
60V											2
110V (125V)											3
220V											4
110VAC											5
230VAC											6
Mounting methods											Position 3
Flush mounting											0
Din rail mounting											1
Secondary language											Position 4
None											0
HUN											1
GER											2

RUS	3
ITA(N/A)	4
FRA	5
ROU	6
ESP	7
Detailed config specific options	
Configuration version	Position 0
Current version	B
Display type	Position 1
B&W	0
3.5" vertical	1
CPU first communication port	Position 2
N/A	0
Fiber optical ethernet MM/ST	1
Fiber optical ethernet SM/FC	2
Fiber optical Ethernet MM/LC	3
RJ-45	4
CPU secondary communication port	Position 3
N/A	0
Fiber optical Ethernet MM/ST	1
Fiber optical Ethernet SM/FC	2
RJ-45	3
Serial POF	4
Serial glass fiber	5
RS-485/422	6
Fiber optical Ethernet MM/LC	7
I/O module in position D	Position 4
O6R5	0
O8	1
O12	2
R8+00	3
R8+80	4
R8+C0	5
R12+0000	6
R12+4000	7

R12+4400	8
I/O module in position E	Position 5
N/A	0
O8	1
O12	2
R8+00	3
R8+80	4
R8+C0	5
R12+0000	6
R12+4000	7
R12+4400	8
O6R5	9
CT module in position B	Position 6
CT+5151	0
CT+5153	1
Type of LD communication	Position 7
Fiber optical SM SH/FC (0-50km)	0
Fiber optical MM/ST (0-2km)	1
IEC61850 protocol (additional charge)	Position 8
No	0
Yes	1
Customization service (additional charge)	Position 9
No	0
Yes	1