

Product Configuration Options

OrderCode:	IED-EP+ S/S24/Variant 5/D3300-C2000500000010-93															
Platform: IED-EP+ S Smart line IED EP+	Type: S24 S24 Smart Line series					Configuration: Variant 5 2 winding transformer differential protection in 24HP industrial enclosure.										
Platform specific options	Position	0	1	2	3	4										
	Value	D	3	3	0	0										
Config specific options	Position	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14
	Value	D	2	0	0	0	5	0	0	0	0	0	0	0	1	0
Checksum	93															
Detailed platform specific options																
Platform version																Position 0
Current version																D
Power Supply																Position 1
24V																0
48V																1
60V																2
110V																3
220/230V																4
I/O modules																Position 2
24V																0
48V																1
60V																2
110V (125V)																3
220V																4
110VAC																5
230VAC																6
Mounting methods																Position 3
Flush mounting																0
Din rail mounting																1
Secondary language																Position 4
None																0
HUN																1
GER																2

RUS	3
ITA(N/A)	4
FRA	5
ROU	6
ESP	7
Detailed config specific options	
Configuration version	Position 0
Current version	C
Type of Power Supply module (S24)	Position 1
PSTP (2xTRIP)	2
Display type	Position 2
B&W	0
3.5" vertical	1
CPU first communication port	Position 3
N/A	0
Fiber optical ethernet MM/ST	1
Fiber optical ethernet SM/FC	2
Fiber optical Ethernet MM/LC	3
RJ-45	4
CPU secondary communication port	Position 4
N/A	0
Fiber optical Ethernet MM/ST	1
Fiber optical Ethernet SM/FC	2
RJ-45	3
Serial POF	4
Serial glass fiber	5
RS-485/422	6
Fiber optical Ethernet MM/LC	7
I/O module in position D	Position 5
N/A	0
O8	1
O12	2
O12+2101	3
O15	4
O6R5	5

R4	6
R8+00	7
R8+80	8
R12+0000	10
R12+4000	11
RTD	13
4xTRIP	17
I/O module in position E	Position 6
N/A	0
O8	1
O12	2
O12+2101	3
O15	4
O6R5	5
R4	6
R8+00	7
R8+80	8
R12+0000	10
R12+4000	11
RTD	13
CT module in position B (TR. Prim.)	Position 7
CT+5151	0
CT+5153	1
CT module in position C (TR. Sec.)	Position 8
CT+5151	0
CT+5153	1
CT terminal type	Position 9
Conventional	0
Ring-lug	1
Generator/Motor differential protection	Position 10
N/A	0
Yes	1
IEC61850 protocol (additional charge)	Position 11
No	0
Yes	1

Customization service (additional charge)	Position 12
No	0
Yes	1
CyberProtect functionality	Position 13
No	1
Yes	2
SW option	Position 14
N/A	0